

**PKC | COMPREHENSIVE HYDRAULIC PULLER KITS**

Capacities from 10 to 50 tonnes

Combination of 4 different pullers in one set

High quality, drop forged steel components



- ▶ Multi-purpose puller kit comprising of grip puller, bearing puller, bearing cup puller and cross head puller
- ▶ Choice of 2-way or 3-way jaw pulling options
- ▶ Incorporates safety overload prevention valve within hydraulic pump

Model	Capacity (tonnes)	Grip Puller Spread of Jaw		Max Reach (mm)	Bearing Puller Spread of Jaw		Bearing Cup Puller Spread of Jaw		Cross Head Puller Spread of Jaw	
		Min (mm)	Max (mm)		Min (mm)	Max (mm)	Min (mm)	Max (mm)	Min (mm)	Max (mm)
PKC10	10	50	350	296	115	260	10	110	40	145
PKC20	20	70	480	320	135	345	12	134	40	145
PKC30	30	90	580	407	180	440	17	255	60	240
PKC50	50	120	920	727	230	580	20	300	60	240

**SCP | SELF-CONTAINED HYDRAULIC PULLERS**

Capacities from 8 to 26 tonnes

Self-contained hydraulic system

Operates in any position



- ▶ Available in 3-jaw configuration only
- ▶ Integrated hydraulic cylinder, pump and puller assembly for easy operation
- ▶ Ergonomic 360° rotating handle for easy positioning during use

Model	Capacity (tonnes)	Type of puller	Piston rod extension (mm)	Max Spread (mm)	Max Reach (mm)
SCP103	8	3-way jaw	50	30	310
SCP203	17	3-way jaw	100	50	430
SCP303	26	3-way jaw	150	100	610

**ACP | AUTO-CENTRE HYDRAULIC PULLER KITS**

Capacities from 10 to 50 tonnes

Quick set-up time, easy to use

High quality, drop forged steel components



- ▶ Self-centering design allows secure positioning of jaws
- ▶ Incorporates safety overload prevention valve within hydraulic pump
- ▶ Supplied as a complete set with all necessary hydraulic components in handy storage case

Model	Capacity (tonnes)	Type of puller	Max Spread (mm)	Max Reach (mm)
ACP10	10	2 & 3-way jaw	350	296
ACP20	20	3-way jaw	480	320
ACP30	30	3-way jaw	580	407
ACP50	50	3-way jaw	920	727

**PKS | HYDRAULIC 2 & 3 WAY PULLER KITS**

Capacities from 4.5 to 50 tonnes

Quick set-up time, easy to use

High quality, drop forged steel components



- ▶ Available in choice of 2 or 3-way puller configurations with 4.5 tonne and 10 tonne models offering a combination of both options
- ▶ Incorporates safety overload prevention valve within hydraulic pump
- ▶ Supplied as a complete set with all necessary hydraulic components in handy storage case

Model	Capacity (tonnes)	Type of puller	Max Spread (mm)	Max Reach (mm)
PKS5-2-3	4.5	2&3-way jaw	240	225
PKS10-2-3	10	2&3-way jaw	350	296
PKS20-2	20	2-way jaw	480	320
PKS20-3	20	3-way jaw	480	320
PKS30-2	30	2-way jaw	580	407
PKS30-3	30	3-way jaw	580	407
PKS50-2	50	2-way jaw	920	727
PKS50-3	50	3-way jaw	920	727



**HI-FORCE HYDRAULIC PULLER KITS**

The Hi-Force range of hydraulic puller kits comprises of self-contained and remote operation, manually operated, 2 and 3-way jaw type pullers, with or without auto-centre option, bearing pullers, bearing cup pullers and cross head pullers, with pulling capacities up to 50 tonnes. All components are manufactured from high strength alloy and drop forged steel.

Additionally, within this section of the catalogue Hi-Force also offers hydraulic pin and bush puller and instalment tool kits, ideally suited for use on heavy duty trucks, earth moving equipment and crane and jib arm lifting equipment, the range offers capacities up to 50 tonnes, at 700 bar maximum working pressure.