





Peinemann



- ▶ Bundle pullers up to 125t capacity (Aerial, Self-propelled, Truck mounted)
- Sales, Service, Rentals



- ▶ Single, Double, Triple, Quadruple, Quintupule lance feeders
- Advanced carbon fibre body, auto indexer



Buldle Lifter

- Designed to ensure safe and effortless bundle lifting
- Minimising the risk of bundle damage during lifting operations, promoting efficiency and reliability.

E H Wachs



Flange Facing Machines

- ID mount Flange facer from 8" to 24 ".
- With optional tool slide up to 36"
- Advanced design with auto prep and auto feed precise end prepping



Pipe Cutting & Bevelling Machines

- ▶ 2" to 72" range split frame cold cutting machines.
- Cutting ,beveling ,counter beveling ,casing cutting, end prepping4 and flange facing



Hand Held Valve Operators

- Operates valves from 6" to 60"
- Forward and reverse variable speed control
- 800ft/lbs of torque

Innotorc







Battery Operated Torque Wrenches

- ▶ Torque range 20 to 8,000Nm in Straight & Angled version with a repeatability of ±3%
- Brushless motor with electronic torque shutoff
- Torque and angle controlled tightening process with digital display in EMAX & EMAWX series
- 60 pre selectable torque settings possible in EMA & EMAW series Predefinition and documentation of tightening process
- via bluetooth possible(EMAX & EMAWX)
- Includes charger and two high-performance lithium-io

Electric Operated Torque Wrenches

- ▶ Torque Range 100Nm to 12,000NM in straight & Angled Version with repeatability of ±3%
- Torque and Angle controlled tightening with digital display
- Presettable customer specific torque values possible as option
- Slim design with low weight
- Fast, Reliable with high performance Gear Box